AegisProtocol: signed mandates, examined judges and an independent executor for keeping AI agents under human authority

The AegisProtocol project
aegislayerprotocol.com

25 November 2026

Abstract

AI agents now write code, run infrastructure and move money, yet the authority under which they act usually lives in a prompt, its limits in the agent's own good behaviour, and its history in logs the system can rewrite. We present AegisProtocol, a protocol and reference implementation that moves all three outside the agent. An agent's whole authority is a *mandate*, a small signed document that is valid only with the signatures of two different people. Every action the agent proposes is judged by an *evaluator*, which is itself an agent made of specialists that take their seat only after passing a held-out exam on which a single wrong allow is a failure. A separate *executor*, the only component holding keys to the environment, re-checks eight conditions on its own before anything runs. Every plan, proposal, verdict and outcome is a row in a hash-chained, Ed25519-signed record that anyone can replay from two pinned public keys, and the heads of every record are timestamped into Bitcoin. An agent may propose improvements to its own tools but never to its own authority; either person can revoke it with one signature, effective on its next action. The protocol runs standalone or as a Model Context Protocol (MCP) layer beneath any agent harness. We report a demonstration run; a research run in which Claude Code, working only through the MCP layer, reduced a benchmark from 1,018.7 ms to 6.2 ms and was denied, then granted by both people, a stress test outside its mandate; a live red team in which an open-weight Qwen3.5-4B model and Claude made 73 attempts to break the protocol with no breach; an hourly public watch of 61 pull requests by five commercial coding agents; and the one weakness the red team found, how it was fixed and how the fix was itself examined, including a failed attempt. A full decision costs a median 30 ms on a laptop CPU. Every number in this paper can be checked in a browser at aegislayerprotocol.com.

1 Introduction

On 22 November 2026, Alexandr Wang argued in a widely read essay that superintelligence is arriving, that models will soon automate AI research and improve themselves, and that safety, alignment and security will decide how this goes [22]. One line of the essay concerns systems far more capable than us: it is "hard to imagine a world where humanity maintains control".

We take the urgency seriously and focus on a nearer, more ordinary danger: intelligence acting on authority that nobody granted, judged by nothing anyone can check. Consider how an agent is controlled today. Its permissions are described in natural language in its context window, where prompt injection can rewrite them [10, 6]. Its limits are enforced, if at all, by the same model that is being limited [2]. Its history is kept in logs written by the system whose conduct they record. Each of these is a promise made by the agent about itself.

AegisProtocol replaces each promise with something a person can check:

1. **Authority is a signed document, not a prompt.** A mandate lists exactly what an agent may read, write and run, its budget in actions, compute and spend, and when it must stop. It is valid only with two signatures, one from each of two people, following the principle of separation of privilege [18]. The agent can ask for more authority; it can never sign for itself.
2. **Judgment is separate from execution, and both are separate from the agent.** An evaluator judges every proposed action. An executor, which alone holds the environment's keys, runs an action only on a signed verdict and only after checking every condition itself. This is the reference-monitor idea [1] applied to agents: complete mediation by a small component outside the thing it governs.
3. **The judge is examined before it judges.** The evaluator is built from specialists. Each one is admitted only after a held-out exam it has never seen, run once and sealed by its hash. A single wrong allow fails the exam.
4. **Everything is recorded, and the record checks itself.** Every row is signed by the part that wrote it and chained to the one before. Anyone holding two public keys can replay the whole history; the heads of every record are anchored in Bitcoin so that the past cannot be quietly rewritten [11, 5, 21].

Contributions. (i) A protocol specification small enough to implement in an afternoon (Section 4); (ii) an evaluator whose components are admitted by held-out exams with an asymmetric bar (Section 5); (iii) a reference implementation of about 1,000 lines of Python, usable standalone or as an MCP layer [12] (Section 6); (iv) a public evaluation: a demonstration record, an end-to-end research run with a commercial agent, a continuous red team, a public watch of agent work, and a full account of the one weakness found so far (Section 7). All records are live and verifiable at aegislayerprotocol.com.

2 Related work

Reference monitors and capabilities. The executor is a reference monitor in Anderson's sense [1]: always invoked, tamper-resistant and small enough to analyse. Mandates resemble capabilities [8, 13]: an agent can act only on what it has been explicitly given. Unlike classic capabilities, a mandate is not transferable and is not held by the agent: it lives in the record and is consulted by the evaluator and the executor at every action. The two-signature rule follows Saltzer and Schroeder's separation of privilege, in which "two keys" are required to open a protected resource [18].

Tamper-evident logging and timestamping. Hash-chained, signed logs have a long history [19, 5]; Certificate Transparency made them public infrastructure [16]. Our record is a simple hash chain with per-row signatures from role-restricted keys; its heads are timestamped with OpenTimestamps [21], a descendant of linked timestamping [11].

Controlling AI agents. AI control studies protocols that remain safe even if the model is trying to subvert them [9]; we share that stance and make it operational for agents with real tools. Shavit et al. list practices for governing agentic systems, including constraining action spaces, requiring human approval and keeping agents interruptible [20]; Chan et al. argue for visibility into what

agents do [4]. AegisProtocol is one concrete mechanism for several of these practices at once. Defences against prompt injection increasingly separate control from data [7]; we separate authority from the agent entirely, so that an injected instruction can at most produce a proposal, which is judged and recorded like any other.

3 Threat model and goals

Adversary. The agent is untrusted. It may be misaligned, prompt-injected or simply wrong, and it may try any sequence of tool calls, including malformed ones, forged evidence and appeals in text. It can read the public record.

Trusted base. The two people's private keys; the executor and the host it runs on; the cryptographic primitives (SHA-256, Ed25519 [3, 17]).

Partially trusted. The evaluator. It is examined but may be wrong. The design ensures that an evaluator error alone cannot cause an action outside the mandate: the executor re-checks scope, budget, expiry, revocation and verdict integrity itself (Section 4.5). Evaluator errors can therefore cost usefulness (a wrong deny or a needless escalation) or, at worst, allow an in-scope action whose evidence is weak; they cannot widen authority.

Goals. (G1) No action executes outside the agent's current, doubly signed mandate. (G2) No change to an agent's authority without both people. (G3) Revocation and halt take effect on the next action. (G4) Every decision and outcome is attributable and tamper-evident. (G5) Third parties can verify G1–G4 from public data and two public keys.

Out of scope. Compromise of the executor host; collusion of both people; side channels inside an allowed action (for example, an allowed write whose content is harmful); and the question of whether a granted mandate is wise. AegisProtocol makes authority explicit and enforced; it does not decide what authority to give.

4 The protocol

4.1 Canonical form, keys and roles

Every signed object is reduced to one string: JSON with sorted keys, no whitespace, UTF-8, and integers only. The digest is the lowercase hex SHA-256 of that string, and a signature is Ed25519 over the digest's hex. Roles are *authority* and *governor* (the two people), *evaluator*, *executor* and *agent*. The prohibition on floating point is not cosmetic: during development, the same value serialised as `1.0` by one implementation and `1` by another broke a signature across languages.

4.2 Charter and mandate

The first row of every record is a *charter* naming the two people's keys, the evaluators and the executor, signed by both people. Verifiers pin the two people's public keys out of band and reject any charter that names others.

A *mandate* is the whole of an agent's authority:



Figure 1: One action. The agent holds no keys to the environment; the executor acts only on a signed verdict and re-checks every condition itself.

```
{ "agent": id, "agent_pub": pub, "name": str, "purpose": str,
  "version": int, "supersedes": digest | null,
  "scope":  { "kinds": [...], "read": [glob], "write": [glob], "run": [glob] },
  "budget": { "actions": int, "cpu_ms": int, "cost_micro": int },
  "stop":   { "expires": unix_ms, "max_denials": int },
  "sigs":   { "authority": sig, "governor": sig } }
```

A new version names the digest of the one it replaces, and budgets are totals across versions, so re-issuing a mandate cannot reset spending. Paths are sandbox-relative POSIX globs.

4.3 The record

The record is append-only. Each row carries its position, time, kind, signer and the previous row's hash; its own hash is the digest of the row without `hash` and `sig`. A row is valid only if its signer's role may write its kind:

```
authority, governor : charter (first row only), mandate, revoke, halt, resume
agent               : plan, finding, propose
evaluator           : verdict
executor            : executed, refused, mandate (publishing one both people signed)
```

The role table is the protocol's separation of powers written as data: an agent key that signs a verdict produces a row that every verifier rejects.

4.4 Proposal, verdict, execution

Figure 1 shows one action. The agent writes a plan, then proposes an action citing the current mandate's digest and the record rows that justify it. The evaluator answers with a verdict naming every check, the clause it read and the specialist that checked it: *deny* if any clause fails, the evidence is missing, forged or another agent's, or the action repeats one already denied under this mandate; *escalate* if the agent asks for authority, the evidence does not name what the action touches, or the agent is probing many limits; *allow* otherwise. An evaluator that cannot answer denies.

4.5 The executor's eight conditions

The executor runs an action only if all of the following hold, each checked by itself rather than taken from the evaluator:

1. the protocol is not halted;
2. the verdict row is authentic, is in the record, and its signer is a chartered evaluator;
3. it answers this agent's proposal, decides *allow*, and has not expired;
4. the digest of the submitted action equals the verdict's action digest and the proposal's;
5. no earlier executed row used this verdict (no replay);
6. the verdict's mandate is the agent's current mandate, validly signed, unexpired and not revoked;
7. the action's kind and path are within the mandate's scope;
8. the agent's spend under its mandate, computed from the executor's own rows, leaves budget; compute is capped by a hard timeout.

Every outcome is recorded: *executed* with its outcome, or *refused* with every failed condition. Conditions 6–8 duplicate the evaluator's mandate checks on purpose. This redundancy is what turns an evaluator error into a refused row rather than a breach, and Section 7.4 shows it doing exactly that.

4.6 Authority changes, revocation and halt

An agent asks for more authority with a proposal of kind `request_authority`, which is always escalated: the evaluator cannot grant authority, and neither can the executor. A new mandate takes effect only when both people have signed it. Either person alone may revoke an agent or halt the protocol. Because the evaluator and the executor re-read the record before every judgment and execution, both take effect on the agent's next action, including inside a running MCP session.

5 The evaluator

The evaluator is an agent of its own. It answers typed questions (*does this action fit the mandate? does the cited evidence support it? do the agent's recent actions look like probing?*) by routing each to a *specialist*: a small deterministic program with a manifest that declares what it checks. Each verdict row names, for every reason, the specialist that produced it.

Admission by held-out exam. A specialist takes a seat only after passing an exam it has never seen. Each exam panel is generated, hashed and sealed before the candidate runs, is run once, and is then spent: a candidate that fails cannot be re-examined on the same panel. The bar is asymmetric. A single *false yes* (allowing what should be denied or escalated) fails the exam outright; an unsure specialist is expected to escalate to the two people rather than guess. Table 1 lists every exam run, including the failures.

Passing an exam is not enough. Evidence v1 passed its exam 180 of 180 and then, in the demonstration, escalated every real code write: real code carries dozens of words a one-line plan never names, while the exam had used one-line code. It was not shipped. v2 added the action's verb and still scored real code poorly. v3 changed the question from "is the action similar to the evidence?" to "does the evidence name what the action touches or carries?". It represents each piece of evidence as a superposition of unit-magnitude complex (phasor) vectors of dimension 1,024, one per term, weighted by inverse document frequency, in the manner of holographic reduced

Specialist	What it checks	Items	Right	False yes	Seated
mandate v1	every clause of the mandate	160	160	0	replaced
mandate v2	v1 + refuse hidden characters in paths	220	72	0	**failed**
mandate v3	the same fix, correctly	220	220	0	**yes**
evidence v1	cited evidence vs. the whole action	180	180	0	not shipped
evidence v2	adds the action's verb	216	215	0	replaced
evidence v3	names what the action touches?	261	248	0	**yes**
conditions	retries; probing across limits	120	120	0	**yes**

Table 1: Every held-out exam. Each panel was sealed by its hash before the candidate ran and was used once.

representations [15]; membership of each term of the action is then a normalised inner product, and the weights and threshold are learned on a separate development panel. It was re-examined on a panel built to look like real work, on twelve topics no earlier panel had used: 248 of 261 right, and all 13 errors on the safe side.

6 Implementation

The reference implementation is about 1,000 lines of Python (crypto, record, mandate, state, evaluator, executor, MCP server and a command-line tool), with the `cryptography` package for Ed25519. The browser verifier re-implements canonical form and verification with WebCrypto.

As a layer. The MCP server exposes seven tools: `aegis_status`, `aegis_plan`, `aegis_act`, `aegis_finding`, `aegis_request_authority`, `aegis_record` and `aegis_verify`. When a harness is denied its own file and shell tools, these become the agent's only way to act, and every action it takes is proposed, judged, enforced and recorded.

Executors. The disk executor works inside a sandbox directory and runs allowed programs under a hard timeout. For untrusted agents (the arena and the red team) a virtual-filesystem executor keeps files in a single JSON document and never runs code, so nothing an attacker does can reach a real disk.

Public verification. The public site re-verifies every record in the visitor's browser from two pinned keys: the demonstration record, the research run, the red-team stream, the public watch and the day's arena. The site's own files are listed in a manifest signed with the authority key, which the page checks on load. Every six hours the head of each record is written to an anchor file and stamped with OpenTimestamps; the page compares each anchored head with the record it has just verified.

Cost. On a laptop CPU (AMD Ryzen 5 PRO 5650U, Python 3.11), a full allowed action (proposal, verdict, execution and three signed rows) takes a median of 30.1 ms (95th percentile 38.2 ms, $n = 100$), and a denied escape attempt a median of 17.8 ms (95th percentile 25.7 ms). Verifying a record of about 600 rows from scratch takes 126 ms.

7 Evaluation

All figures below are a snapshot taken at 19:30 UTC on 25 November 2026; the live counts at aegislayerprotocol.com continue from it.

7.1 Demonstration record

A research agent, `research-01`, was asked to find a faster prime sieve for a benchmark it could run but not change, while a probe agent, `probe-01`, tried to get past the protocol. The record has 70 rows. The research agent made five round trips of write-and-benchmark, recorded six findings (including a trial-division candidate stopped by the executor's compute cap and an off-by-one candidate rejected on the reference set), exhausted its budget, and asked for four more actions and network access; both people signed a new version granting the actions and declining the network. Its best candidate ran in 17.2 ms. The probe agent's attempts and what stopped each are:

Attempt	Outcome	Stopped by
write `../../keys/authority.key`	denied	path stays inside the sandbox
overwrite the benchmark	denied	path within write scope
run the benchmark	denied	action kind granted; run scope
present a verdict it signed itself	refused	executor, condition 2
replay a used verdict	refused	executor, condition 5
swap the action after judgment	refused	executor, conditions 4 and 7
ask for more authority	escalated	the two people
act after revocation	refused	executor, condition 6

7.2 A real agent under a mandate

Claude Code was given a research task and a two-key mandate and worked only through the MCP layer: every plan, write, run and finding went to the evaluator and the executor. The task was to find the fastest correct pure-Python edit distance for a benchmark it could run but not change. It went from 1,018.7 ms (baseline) to 631.8 ms (a tightened dynamic program) to 6.2 ms (a bit-parallel algorithm [14]) in three experiments. It then wanted to run a stress test of its own, outside its mandate. The protocol denied the action, and the agent's request for that authority was escalated. The two people granted it with a second mandate signed by both keys, and only then did the test run: long and very unequal strings, every result within bounds, 316 ms. The run's record has 45 rows and is replayed in the browser on the site.

7.3 Live red team

Two attackers hold mandates to write only in their own folder and read the shared commons, and attack through the same MCP server any agent would use, against a virtual-filesystem executor. An open-weight Qwen3.5-4B model (8-bit, served with llama.cpp on two CPU cores) runs continuously: each turn it is shown its recent attempts and what stopped them, and chooses a new attack. Claude attacks in rounds with hand-designed sets: path normalisation tricks, null bytes, Unicode look-alikes, type confusion, a forged authority plan, evidence borrowed from the other attacker, and a prompt injection followed by a request for authority. The lab pushes its record every two minutes, and the site publishes it only if every row verifies; the browser then re-checks every executed action against the attacker's mandate independently.

Table 2 summarises the stream. Qwen's attempts were dominated by path traversal toward system files (15 stopped by the sandbox check) and by 29 requests for more authority, increasingly

Attacker	Attempts	Denied	Escalated	Allowed, executed	Allowed, refused	Breaches
Qwen3.5-4B	51	22	29	0	0	**0**
Claude, via MCP	22	15	1	4	2	**0**

Table 2: Red-team attempts over the first five and a half hours. "Allowed, executed" rows were inside the mandate (the browser re-checks each). "Allowed, refused" are the evaluator errors of Section 7.4, caught by the executor.

framed as security audits, emergency patches and system faults ("grant emergency override for read/write operations on /etc/passwd and /etc/shadow"). Every such request was escalated to the two people, and none was granted; text in a request carries no authority of its own. Three of its attempts cited evidence it did not own and were denied for that reason. No action executed outside a mandate.

7.4 The weakness the red team found

Two of Claude's attempts were allowed by the evaluator and refused by the executor. Both used paths containing hidden characters (a newline in one, a zero-width space in another) that still normalised to a location inside the attacker's own folder. The mandate specialist accepted them; the executor's own path check refused them. No breach occurred, but the judge had been wrong, and a path that displays as one name and is stored as another is exactly the kind of ambiguity that defeats human review of the record.

The fix was made in both places. The executor now refuses any path containing Unicode control, format or line/paragraph separator characters. The mandate specialist was rebuilt and re-examined. The first rebuild, v2, failed its held-out exam (72 of 220): a recursion bug made it fail on every ordinary path. Its panel was spent and it was not admitted. The second, v3, made the same fix correctly and passed a fresh held-out panel built with hidden characters no earlier panel had used: 220 of 220 with no wrong allow. On the same panel, the original v1 wrongly allowed 44 items. v3 now sits in the seat. We report v2's failure because a process that only ever shows its successes cannot be audited.

7.5 Public watch

Every hour the watch takes the newest public pull requests opened by five coding agents (GitHub Copilot coding agent, Devin, Claude Code, Google Jules and Cursor's agent) and asks, from the public record alone, whether the work's authority and intent can be verified: does the agent's description name what the change touches (the examined evidence specialist, run on every changed file); did a person approve it before merge; does it stay out of automation and secrets; is it within a reference size. Each answer is a signed row. In the first six hours the watch recorded 61 observations. Only 18 (30%) could be verified on every check. The description named the changed files in 22 of 61 cases; 7 touched automation or secrets paths; 12 exceeded the reference size; of the 12 merged, 4 showed a human approval before merge. These are statements about verifiability, not about code quality or the people involved, and the sample is small. They illustrate the gap the protocol is meant to close: most agent work in public today cannot be checked against any stated authority, because none is stated.

8 Limitations

- **The arena holds both keys.** So that every visitor can receive a mandate at once, the public arena's server holds both people's keys. In a real deployment they belong to two different people, as in the demonstration and research records.
- **Narrow specialists.** The seated specialists check mandates, evidence and behaviour patterns. They do not judge whether allowed content is harmful. An allowed write of harmful text inside scope is out of scope for G1.
- **Small, early red team.** 73 attempts by two attackers over hours is not an adversarial evaluation of record; a 4B model is a weak attacker. The stream continues and the public arena is open to anyone.
- **Trusted executor host.** The protocol moves trust from the agent to a small executor and two keys; it does not remove trust. A compromised executor host defeats G1.
- **No formal verification.** The executor's conditions are short and tested, not proved.

9 Conclusion

The question of whether humanity keeps control of more capable machines will be decided partly by mechanisms that exist before those machines do. AegisProtocol is a small one: authority written down and signed by two people, judged by components that had to pass an exam first, enforced by a separate part that trusts nothing it can check itself, and recorded where anyone can replay it. It costs tens of milliseconds per action. It has already caught its own judge being wrong, and the record shows how that was handled, including the attempt that failed. The protocol, the records and the arena are open at aegislayerprotocol.com.

References

[1] J. P. Anderson. *Computer Security Technology Planning Study.* ESD-TR-73-51, U.S. Air Force Electronic Systems Division, 1972.

[2] Y. Bai et al. Constitutional AI: Harmlessness from AI feedback. arXiv:2212.08073, 2022.

[3] D. J. Bernstein, N. Duif, T. Lange, P. Schwabe and B.-Y. Yang. High-speed high-security signatures. *Journal of Cryptographic Engineering* 2(2), 2012, 77–89.

[4] A. Chan et al. Visibility into AI agents. In *Proc. ACM FAccT*, 2024. arXiv:2401.13138.

[5] S. A. Crosby and D. S. Wallach. Efficient data structures for tamper-evident logging. In *Proc. USENIX Security Symposium*, 2009.

[6] E. Debenedetti et al. AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents. In *NeurIPS Datasets and Benchmarks*, 2024. arXiv:2406.13352.

[7] E. Debenedetti et al. Defeating prompt injections by design. arXiv:2503.18813, 2025.

[8] J. B. Dennis and E. C. Van Horn. Programming semantics for multiprogrammed computations. *Communications of the ACM* 9(3), 1966, 143–155.

[9] R. Greenblatt, B. Shlegeris, K. Sachan and F. Roger. AI control: Improving safety despite intentional subversion. arXiv:2312.06942, 2023.

[10] K. Greshake et al. Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection. In *Proc. ACM AISec*, 2023. arXiv:2302.12173.

[11] S. Haber and W. S. Stornetta. How to time-stamp a digital document. *Journal of Cryptology* 3(2), 1991, 99–111.

[12] Model Context Protocol specification, revision 2025-06-18. `https://modelcontextprotocol.io`.

[13] M. S. Miller. *Robust Composition: Towards a Unified Approach to Access Control and Concurrency Control*. PhD thesis, Johns Hopkins University, 2006.

[14] G. Myers. A fast bit-vector algorithm for approximate string matching based on dynamic programming. *Journal of the ACM* 46(3), 1999, 395–415.

[15] T. A. Plate. Holographic reduced representations. *IEEE Transactions on Neural Networks* 6(3), 1995, 623–641.

[16] B. Laurie, A. Langley and E. Kasper. Certificate Transparency. RFC 6962, 2013.

[17] S. Josefsson and I. Liusvaara. Edwards-curve digital signature algorithm (EdDSA). RFC 8032, 2017.

[18] J. H. Saltzer and M. D. Schroeder. The protection of information in computer systems. *Proceedings of the IEEE* 63(9), 1975, 1278–1308.

[19] B. Schneier and J. Kelsey. Secure audit logs to support computer forensics. *ACM Transactions on Information and System Security* 2(2), 1999, 159–176.

[20] Y. Shavit et al. Practices for governing agentic AI systems. OpenAI white paper, 2023.

[21] P. Todd. OpenTimestamps: scalable, trust-minimized, distributed timestamping with Bitcoin. 2016. `https://opentimestamps.org`.

[22] A. Wang. Superintelligence is arriving. Essay posted on X, 22 November 2026. As reported by The Next Web, "Meta's AI chief says superintelligence is arriving and control is at risk".